



# HN30005E3C / E4C

HN Series – Natural Gas / LP

*Keeping Idaho Clean and Green*

## Steam / Hot / Cold Water Pressure Steamer – Natural Gas or LP Heated, Electric Motor

The **HN Pro Line® Series** is a heavy-duty stationary unit offering high output and instant cleaning power with adjustable temperature for various cleaning applications. The Stainless Steel enclosure offers lifetime corrosion resistance and accessibility to components. High torque / low RPM belt driven pump ensures years of worry free service with built in overheat protection if machine is left on. The automatic electronic ignition eliminates the need to manually light a pilot and increases the safety of the machine.

<b>PRESSURE</b>	3000
<b>FLOW CAPACITY</b>	4.8
<b>OUTLET TEMP</b>	Adjustable to 250°F (130 °F rise)
<b>POWER/ENGINE</b>	10 hp
<b>VOLTS/PHASE/AMPS</b>	E3H is 208v/230v / 3ph / 30amp      E4H is 460v / 3ph / 14amp
<b>CONTROLS/SWITCHES</b>	Lighted rocker switches, panel mounted soap control, adjustable thermostat
<b>PUMP</b>	CAT pump, Triplex Ceramic Plunger
<b>POWER DRIVE</b>	V-Belt Drive with Integrated Tension Adjustment
<b>PRESSURE CONTROL</b>	K-7 Total Relief with <i>By-Pass Cool</i> System / Safety Relief Valve and Burst Disc
<b>WATER SUPPLY</b>	4 Gallon Float Tank with Double Filtration and Back Flow Prevention
<b>PRESSURE HOSE</b>	3/8 x 50' Steel Wire Braided / 250°F 3000 psi Rated
<b>GUN/WAND</b>	48" molded insulator wand, with quick coupler
<b>SOAP INJECTION</b>	Full Chemical Pressure Injection, Precision Stainless Steel Metering Valve
<b>NOZZLE</b>	#5.5 (0°, 15°, 40°), #4.5 (25° Steam)
<b>BURNER COIL</b>	½" x 220' Schedule 80, 7 Pancake, Ceramic Insulation and Stainless Steel Wrap and Cap
<b>BURNER/POWER</b>	Natural Gas with Auto Ignition and 90 Second Safety Lockout, Cast Iron Ring, Brass Jets
<b>BURNER INPUT</b>	440,000 BTU
<b>CONSTRUCTION</b>	Powder coated support base and frame, stainless steel wrap, cover and panels
<b>WHEELS</b>	Wheel kit option available for LP version
<b>WEIGHT/DIMENSION</b>	492#, 47x48x24

\*Specifications subject to change without notification and may vary due to ambient conditions.

### Featuring:

- ✓ **Adjustable Thermostat** with steam setting for various cleaning applications
- ✓ **By-Pass-Cool** system protects pump from overheating if left on after use
- ✓ **24 Volt Automatic Ignition** system on low emission natural gas burner

### Options...

Hose Reels (AR008, AR187, AR188) Draft Diverter (BGD10), Multiple wash station shut-off (ACW20), Wind-up remote timer (AEN80), LP Conversion (BGV05), Wheel Kit for LP version (AHB12), Hour Meter kit (EM620)



208-459-3645 fax

208-459-3464 phone

Email [sales@vikingindustrial.com](mailto:sales@vikingindustrial.com)

[www.vikingindustrialsystems.com](http://www.vikingindustrialsystems.com)