



# ProTowWash Trailers

**MOBILE SELF-CONTAINED WATER TANK TRAILER SYSTEM**



Shown with SS Series skid on ProTowWash model T400 with stainless swing out hose reels

**SELECT THE SET-UP THAT IS RIGHT FOR YOU**

# ProTowWash® Trailers

DESIGNED TO MATCH YOUR HYDRO TEK WASHER PERFECTLY

Portrays a professional image to your customers and frees up your tow vehicle for other tasks.

#### Powder Coated Steel Frame:

The frame is constructed with a heavy-gauge steel structural tube spine for extra rigidity.

#### Suspension:

Torflex axles deliver up to 300% more wheel travel than leaf spring axles to create a smooth ride over rough terrain. This adds to the life of your power washer and reduces fatigue on your tow vehicle. T300EE, T400EE, T500EE have electric brakes on both axles to comply with commercial use D.O.T.

#### Tank:

Choose from trailers with 200 gallons up to 540 gallons of water storage. Hydro Tek's exclusive seamless polyethylene supply tanks with hold down straps provide secure water storage. Dual tanks on the 400 and 540 gallon trailer provide baffling to reduce water sloshing and also allows for the water tank to be split to carry two different types of fluid.

#### Lights/Wiring:

Tail lights are water tight sealed and recessed for added protection from road hazards. All wiring is routed through the trailer spine to eliminate damage from road hazards. Electric brake trailers have a brake controller ready 7-prong plug.

#### Storage:

The integrated storage tube for spray wands and large (47" x 22" x 10") storage box at the rear end of the trailer offers ample area to store wands, hoses and other accessories. Optional integrated soap pail racks are also available.

#### Coupler/Chains/Jack:

Save time every time you hook up the trailer to your tow vehicle with an oversized wheel that allows for easy movement of the trailer. All trailers include safety chains and a wheeled jack that quickly swings up and out of the way.

#### Water Filter/Valves/Hoses:

High capacity water filter with 1½" water drain valve supplies clean water to the pump to increase pump life. Complete plumbing and hoses, sized properly to your Hydro Tek Washer, are included. Hoses are routed through grommets in the trailer frame to protect from chaffing and road hazards.

#### Customize with your choice of accessories:

3-way ball valve, Stainless advertising panels, Stainless Hose Reels, Light Bar, Bucket/Chemical Rack, Chrome Wheels, Machine Cover, sand hopper, chemical tank, Custom trailer color, alternative hitch choices, locking storage, Hydro Vacuum filtration systems



Optional stainless, pivoting hose reel swings to five positions for convenient hose use in any direction.



Recover and Reuse your wash water with the addition of a Hydro Vacuum® trailer mounted filtration system.



Shown with optional accessories. Your choice of SS, SC, or SCU Series power washer, sold separately



### Specifications

Model	Capacity	Axle	GVWR	Brakes	Class <sup>1</sup>	Length
T200N	200 Gallons	Single	3500#	None	II	125"
T200E	200 Gallons	Single	3500#	Electric	II	125"
T250E +	270 Gallons	Single	3500#	Electric	II	125"
T300N	270 Gallons	Tandem	4400#	None	III	130"
T300S	270 Gallons	Tandem	4400#	Surge	III	130"
T300EE	270 Gallons	Tandem	4400#	Electric	III	130"
T400S	400 Gallons*	Tandem	5000#	Surge	III	156"
T400EE	400 Gallons*	Tandem	5000#	Electric	III	156"
T500S	540 Gallons**	Tandem	7000#	Surge	IV	168"
T500EE	540 Gallons**	Tandem	7000#	2) Elect	IV	168"
<b>Dual SC Skid Trailers (available through special order dept)</b>						
T50DS	270 Gallons	Tandem	7500#	Surge	IV	168"

#### Tank Skids

T185T	200 Gallons	For SS, SC, and SCU skids	74"
T270T	270 Gallons	For SS, SC, and SCU skids	80"

+ For SS Series skids only

\* Equipped with (2) 200 gallon tanks \*\* Equipped with (2) 270 gallon tanks

<sup>1</sup>Class II = 3500#, Class III = 5000#, Class IV = 7500#

Specifications may vary, consult factory for custom models

Check your local or state entities for trailer brake requirements.



Keeping Idaho Clean and Green

208-459-3464 phone 208-459-3645 fax  
Email: [sales@vikingindustrial.com](mailto:sales@vikingindustrial.com) [www.vikingindustrial.com](http://www.vikingindustrial.com)