



Keeping Idaho Clean and Green

HD22004E2H

HD Series – Pressure Steamer

Steam / Hot / Cold Water – Diesel Heated, Electric Motor

The **HD Series** offers rugged, dependable, affordable service. It features a heavy-duty stainless steel frame with pneumatic wheel kits standard, handles, panels and coil protection – offering lifetime corrosion resistance. Panel mounted temperature control offers the benefits of high pressure cleaning with water temperature from cold through full Steam Settings. Panel mounted controls allow the operator to vary the mixture of soap, or other additives for optimal cleaning effectiveness. High efficiency dual pass coil and large capacity diesel fuel tank offer up to 8 hours of operation between refueling. Ideal for farm and agricultural applications, auto repair shops, and wherever sanitizing and degreasing are needed.

PRESSURE	2200psi
FLOW CAPACITY	3.5gpm
OUTLET TEMP	Adjustable to 250°F (120 °F rise)
POWER/ENGINE	5.0 hp Instant Trigger Start/Stop
VOLTS/PHASE/AMPS	Dual rated for 208v or 230v / 1ph / 24a
POWER CORD	35' cord with Ground Fault Circuit Interrupter for additional safety
CONTROLS/SWITCHES	Lighted rocker switches, adjustable thermostat
PUMP	AR pump, Solid Ceramic Plungers, Brass head, Stainless steel valves
POWER DRIVE	V-Belt Drive, Low RPM – Cooler, quieter, continuous duty performance
PRESSURE CONTROL	Adjustable Pressure Unloader, Safety Relief Valve, Burst Disc
WATER SUPPLY	Pressure Fed
PRESSURE HOSE	3/8" x 50' Steel Wire Braid Hose, 3000 psi, 250°F Rated
GUN/WAND	Insulated Shut Off Gun / 36" Wand w/ Nozzle Quick Connector
SOAP INJECTION	Downstream soap/chemical injection, activated with soap nozzle
NOZZLE	#4.5(15°) #3.5(25°) and 40° Soap nozzle
BURNER COIL	½" Sch 80 Coil, Stainless Steel Coil Enclosure, Dual Pass, High Efficiency
BURNER/POWER	Beckett Oil Fired, Automatic Ignition, Forced Draft, Inline fuel filter
BURNER FUEL/CAP	Diesel fuel #1 or #2, Kerosene, Stove oil, JP8 fuel, 8 gal. capacity, up to 8hrs. run time
FRAME CONSTRUCTION	Stainless steel frame, coil wrap, and panels
WHEELS	4) 10" foam filled wheels installed
WEIGHT/DIMENSION	360#, 47x29x36

*Specifications subject to change without notification and may vary due to ambient conditions.



Featuring:

- ✓ **High Efficiency Heater** – Unique Dual Pass coil, with double wall stainless steel insulation, capture heat on both sides of the Schedule 80 pipe to burn less fuel.
- ✓ **Flexible, Effective Cleaning** – Adjustable temperature with steam setting and soap/chemical injection delivers more cleaning power over a wide range of applications.
- ✓ **Compact and Portable** – Wheels included. Easily moved to wherever you need to clean
- ✓ **Instant Startup and Shut down** – I.T.S. Instant Trigger Start and stop, avoids risk of pump overheating, expensive thermal damage, and saves electricity

Options...

Stainless Steel Hose Reel (AR003)



208-459-3645 fax

208-459-3464 phone

Email sales@vikingindustrial.com

www.vikingindustrialsystems.com